

Commercial Energy Series

Compact and powerful electric vehicle charging solution



Ward Energy Series is designed to be the ultimate electric vehicle charging solution. At up to eight times faster than a standard 110v plug, the Energy Series safely delivers up to 25 miles of driving range for every hour of charge time.

With its adjustable power output, you can have the ideal power to match your supply panel, electric vehicle and driving range. The Energy series chargers will charge all plug-in vehicles sold in the US and Canada.

An attractive, powerful and durable Level 2 charger, the Commercial Energy Series features a slim, durable design that is outdoor rated. Available in multiple mounting configuration options, the streamlined Energy Series has as a small footprint, whether wall or pedestal mounted.

We back up our Energy Series with a 3-year warranty and offer a reasonably priced optional 5-year plan.

Open access version, common for fleet use

- ✓ Powerful Level 2 with 7.6kW output, adjustable to 5.8kW or 3.8kW
- ✓ 25' cable standard
- ✓ Easy plug-in installation or hardwire for outdoor install
- ✓ 3-year warranty with optional 5-year
- ✓ UL & cUL safety certified
- ✓ All-weather durability
- ✓ Slim, attractive design

Charger with optional pedestal and optional retractors

KEY BENEFITS

- Up to 8 times faster than a standard 110v plug
- Up to 25 miles of driving range for every hour of charge time
- Adjustable power output
- Charges all plug-in vehicles sold in the US and Canada



UL-listed and meets safety criteria for use throughout North America



Energy Series EV Charger



Ward FCTs and Fuel View software are compatible with EV chargers for controlling access and tracking usage.

Specifications

Voltage (Vac)	208/240VAC, Single phase
Frequency (Hz)	60 Hz
Current (Rms)	Adjustable: 16A/24A/32A (3.8kW/5.8kW/7.6kW)
Circuit Breaker	16A=20A/24A=30A/32A=40A
Charging Connector	SAE J1772
Charging Cable Length	25 ft.
Display	Color LED Status lights Character height: 116 * 8.5 * 37, 5.57 (L*W*H mm) Dot matrix: 5*8 OLED: 20x2
Temperatures	Operating: -30°C/-22°F to 50°C/122°F Storage: -40°C/-40°F to 70°C/158°F
Mounting	Wall mount / Pedestal mount
Wiring	Hard-wired
IP Performance	NEMA 4
Impact Resistance	IK10
Dimensions	7.56 x 3.11 x 11.14 (WxDxH inches) <i>Optional</i> Pedestal Post: 6 x 6 x 60 (WxDxH inches), Pedestal Base: 12 x 12 (inches)
Pedestal Construction	Aluminum, grey powder-coat finish, stainless steel hardware
Certification	UL 50/991/1449/1998/2231/2594



Available in multiple configurations: single-port, wall or pedestal, dual-port pedestal, cable retraction

Charging plug

Contact

www.ejward.com/contact