

Tank Level Sensors

Mini-Me[™] Universal Remote Display



KEY FEATURES

- Remotely view leak sensor alarms and tank inventory in up to 16 tanks
- Connects to any industry standard ATG
- Allows main ATG installation in convenient, economical locations
- Audio and visual alarms
- Easy to install and easy to use
- Wall mount or flush mount
- 7 inch color touch screen graphic display
- Wide viewing angle

Options

• Wireless communication

PROTEUS Mini-Me is a color graphic display providing automatic tank gauge (ATG) users the access current tank gauging, leak detection and alarm status from ATG consoles.

ATGs monitor storage vessels for level, temperature, volume and potential leaks, and due to installation constraints are typically located where audio visual alarms and level information are not conveniently accessible or are out of the operator's normal work area, potentially rendering alarms to go unnoticed. These ATGs are often difficult to use and understand.

The PROTEUS Mini-Me allows the user to easily and intuitively gain access to ATGs and level information anywhere throughout a facility. It provides both wired and wireless access to industry standard ATG's providing easily accessible information where required.



See the Ward Brochure for our Solutions Overview.



Specifications

Electrical	100-240 VAC ±10%		
	50/60 Hz 25 watts (12 VDC power available upon request)		
Audio Visual Controls		7-inch color graphic display touch screen	
	Audible alarm	85 dB piezoelectric horn	
	System status	3 LED's (OK, warning, alarm)	
Accessories	WRS-232	Wireless RS-232 link includes both tank gauge and remote transceivers	
	WRS-232R	Wireless RS-232 repeater for extendingWRS-232 wireless reach	
	RD-PCK	Power cord kit	
	RD-232C-75	75 feet RS232 cable	
	C232-422-RD7	CTS RS-232-422 booster kit to increase distance of RS-232 output	
	ENC-4X-RD7	NEMA 4X enclosure	
	HTR-1	Heater for NEMA 4X enclosure	
	TEM-CS	Thermostat for NEMA 4X enclosure	
Weight	5 lb		
Dimensions	7 x 8 x 3 inches (H x W x D)		



Proteus Mini-Me screen samples



Contact

Dimensions may vary slightly. Specifications subject to change without notice, verify with manufacturer.

PROTEUS Mini-Me (12/19)



www.ejward.com/contact